





## **Portland Pozzolana Cement**

Despatched during Week No.		41	From	08/10/18		То	14/10/18
Test Certificate No.		41	Reference	e No.		WCW/IMS/QA/FM/09	
Dated		12/11/18	Reference				
S.N.	Pa	arameters	Results Obtained	Requirement as per IS 1489 (Part I) : 2015			
1	Chemical Composition						
	Loss on Ignition (% by mass)			2.00	Not More than 5.0 %		
	Magnesia (% by mass)			0.80	Not more than 6.0 %		
	Sulphuric Anhydride SO3 (% by mass)			2.80	Not More than 3.5 %		
	Chloride Content (% by mass)			0.01	Not more than 0.1 % for general purpose & not more than 0.05 % for pre-stressed structures		
	Insoluble Residue (% by mass)			26.20	Not More than [X + 4.0 (100-X) / 100] & Not less than (0.6 X), Where "X" is the declared Pozzolana content in cement		
	Physical Analysis						
2	Fineness						
	Blaine's Specific Surface Area (m <sup>2</sup> / kg)			330	Not Less th	nan 300	
3	Compressive Strength (MPa)						
	72 ± 1h (3 Days)			28.0	Not less than 16.0		
	168 ± 2h (7 Days)			38.3	Not less than 22.0		
	672 ± 4h (28 Days) *			55.7	Not less than 33.0		
4	Setting Time (Minutes)						
	Initial			125	Not less than 30		
	Final			220	Not more than 600		
5	Soundness						
	Le-Chatelier Expansion (mm)			1.00	Not more than 10.0		
	Auto-Clave Expansion (%)			0.010	Not more than 0.8		
6	Drying Shrinkage (%)*	(%)*			Not more than 0.15		
7	Normal Consistency (%)			30.00			
	Temp. During Testing ( <sup>0</sup> C)			27.00	$(27 \pm 2)^{0}$ C		

\* Fly Ash Content in Cement is (%)

30.00

The above cement complies with the requirements of IS 1489 (Part I): 2015 for Portland Pozzolana Cement.

Current t

Manager (QA)

Registered Office: Cement House, 121, Maharishi Karve Road, Mumbai - 400020